

Maintenance Main Items

If a Maintenance Minder indicator does not appear more than 12 months after the display is reset, change the engine oil every year.

NOTE: Adjust the valves during services A, B, 1, 2, or 3 if they are noisy.

Symbol	Maintenance Main Items
A	Replace engine oil — Engine oil capacity without oil filter <ul style="list-style-type: none"> 1.5 L engine: 3.2 L (3.4 US qt) 2.0 L engine: 4.4 L (4.6 US qt)
B	Replace engine oil and oil filter — Engine oil capacity with oil filter <ul style="list-style-type: none"> 1.5 L engine: 3.5 L (3.7 US qt) 2.0 L engine: 4.8 L (5.1 US qt)
	Inspect front and rear brakes <ul style="list-style-type: none"> Check pads and discs for wear (thickness), damage, and cracks. Check calipers for damage, leaks, and tightness of mounting bolts.
	Check expiration date of the tire repair kit bottle (if equipped)
	Inspect tie-rod ends, steering gearbox, and gearbox boots <ul style="list-style-type: none"> Check steering linkage. Check boots for damage and leaking grease.
	Inspect suspension components <ul style="list-style-type: none"> Check bolts for tightness. Check condition of ball joint boots for deterioration and damage.
	Inspect driveshaft boots — Check boots for cracks and boot bands for tightness.
	Inspect brake hoses and lines including VSA lines — Check master cylinder and VSA modulator-control unit for damage and leakage.
	Inspect all fluid levels and condition of fluids <ul style="list-style-type: none"> Engine coolant M/T fluid CVT fluid A/T fluid Clutch fluid Brake fluid Windshield washer fluid
	Inspect exhaust system * — Check catalytic converter heat shields, exhaust pipes, and muffler for damage, leaks, and tightness.
	Inspect fuel lines * and connections * — Check for loose connections, cracks, and deterioration; retighten loose connections and replace damaged parts.

NOTE: According to state and federal regulations, failure to do the maintenance items marked with an asterisk (*) will not void the customer's emissions warranties. However, Honda recommends that all maintenance services be done at the recommended interval, to ensure long-term reliability.